

UN Certified ALC

Conforming to UN standards and approved for the transport of dangerous materials within packaging groups I, II, & III our UN Certified Attached Lid Containers are used by waste management and disposal companies with an integrated strap to secure dangerous goods within.

Key Benefits



Increase vehicle fill up to 10%
The UN certified container adopts our innovative ALC lid design with 100% tessellation, capable of saving up to 10% when storing or transporting empty containers.



Integrated Straps
Integrated straps permanently fixed to the container enable easy UN level containment & safety for hazardous materials.



Compatible with the Pally and Lid System
The UN certified range works in conjunction with the pally and lid for ultimate security and manoeuvrability of hazardous materials.



Certified for solids and liquids
Each of the UN Certified containers can be used to transport Liquids with the use of an insertable UN Certified Bag.



Certified to your needs
If you have specific needs we can develop a UN grade solution for you.



Multiple footprints & sizes available
With a choice of multiple footprints and size configurations, we're sure to have a container to suit your needs.

Accessories & Options



ALC Label Holder
Identification features such as barcode and RFID labelling can be provided for tracking your goods.



ALC Security Seals
Security seals available for various levels of security requirements.



Approved Inner Bag
(Minimum 90 Microns) & security seal



Product configuration

We offer special product configurations to ensure the solution provided is the best possible solution for you.



Standard Stock Colours



Pantone 021 C
HV Orange

Favoured Colours (MOQs Apply)



Pantone: 293 C
Blue



RAL: 6018
Yellow Green



Pantone: 109 U
Yellow



RAL: 3020
Traffic Red



RAL: 7016
Slate Grey



RAL: 5015
Sky Blue



RAL: 9004
Signal Black



RAL: 7040
Tele Grey - 1

Specification sheet

All dimensions are nominal and subject to manufacturing tolerances.

Container footprint (mm)	600 x 400
Container height (mm)	365
Material	High impact polypropylene
External top (mm) length x width	600 x 400
External base (mm) length x width	526 x 350
Internal top (mm) length x width	547 x 371
Internal base (mm) length x width	521 x 346
Nesting pitch (mm)	108
Usable height (mm)	330
Capacity (Litres)	63
Weight (kg)	3.0
Certified MAX payload (kg)	45
Pallet type	UK
Quantity on pallet	85
Pallet height (m)	2.24