

Attached Lid Container - 64 Litre Totebox

The 64 Litre Totebox is the original ALC featuring an innovative tessellating lid design, reducing the likelihood of damage and allowing for greater logistics gains and increased vehicle fill.

Key Benefits



Increase vehicle fill up to 10%
The ALC 64 Litres' nesting lids provide complete tessellation saving room when stacked in comparison to inefficient competitor lids and increase vehicle fill when returning empties.



Snap fitting lids
The quick and easy snap-fitting lids aid stock management and enable quick damage replacement.



Reduced likelihood of damages
The lids do not overhang due to the unique patented design reducing damages when stacking the container.



Pally and Lid compatible
All of our containers work in conjunction with the Pally & Lid system to provide the ultimate RTP solution, completely eliminating one-trip packaging.



Swap out scheme
We offer the opportunity to swap any old, damaged or unwanted containers in part exchange.

Accessories & Options



ALC Label Holder
Identification features such as barcode and RFID labelling can be provided for tracking your goods.



ALC Security Seals
Security seals available for various levels of security requirements.



Product configuration

We offer special product configurations to ensure the solution provided is the best possible solution for you.

Standard Stock Colours



Favoured Colours (MOQs Apply)



Digital & Hot Foil Printing

Position: Central on long side
Max Size Digital: 85mm (H) x 290 mm (W)
Max Size Hot Foil: 175mm (H) x 260 mm (W)

Specification sheet

All dimensions are nominal and subject to manufacturing tolerances.

Helios height (mm)	365
Material	High impact polypropylene
External top (mm) length x width	600 x 400
External base (mm) length x width	526 x 350
Internal top (mm) length x width	547 x 371
Internal base (mm) length x width	521 x 346
Nesting pitch (mm)	108
Usable height (mm)	330
Capacity (Litres)	63
Weight (kg)	3.0
Payload static (kg) repro / virgin	35 / 50
Payload dynamic (kg) repro / virgin	20 / 35
Stacking load static (kg) repro / virgin	250 / 350
Stacking load dynamic (kg) repro / virgin	125 / 175
Temp resistance	-20°C to +40°C
Pallet type	UK
Quantity on pallet	85
Pallet height (m)	2.24