Attached Lid Container - Mini

The smallest ALC within the range with an innovative hinge-pin design, maximizing the security of goods within, and a textured base designed to reduce noise pollution on conveyor systems.

Key Benefits



Secure hinge pin design This concealed hinge pin offers an increased level of security protecting high value goods within.



Working with automation systems The Mini has a collar design to work in conjunction with automation machinery within supply chains today.



Secure Banding Non-slip ribbing on the Lid assures banding is secure.



Textured base The textured base is designed to prevent unwanted movement on conveyor systems which can cause delays in automation lines. Automation sensors can also sometimes bounce off a base if it's not textured.



Easy label remove ribbing

The ribbed area on the side of the 400 x 300 is designed to make label removal easier and faster.

Accessories & Options



ALC Label Holder Identification features such as barcode and RFID labelling can be provided for tracking your goods.



ALC Security Seals Security seals available for various levels of security requirements.



Product configuration

We offer special product configurations to ensure the solution provided is the best possible solution for you.


Standard Stock Colours

RAL: 9004

Signal Black


Favoured Colours (MOQs Apply)















Digital & Hot Foil Printing

Position: Max Size Digital: Max Size Hot Foil: Central on long side 85mm (H) x 290 mm (W) 85mm (H) x 260 mm (W)

Specification sheet

All dimensions are nominal and subject to manufacturing tolerances.

Height (mm)	Mini
Material	High impact polypropylene
External top (mm) length x width	400 x 300
External base (mm) length x width	350 x 257
Internal top (mm) length x width	363 x 270
Internal base (mm) length x width	345 x 252
Nesting pitch (mm)	108
Usable height (mm)	287
Capacity (Litres	25
Weight (kg)	1.92
Payload static (kg) repro / virgin	35 / 50
Payload dynamic (kg) repro / virgin	20 / 35
Stacking load static (kg) repro / virgin	250 / 350
Stacking load dynamic (kg) repro / virgin	125 / 175
Pallet type	UK
Quantity on pallet	153
Pallet height (m)	Max 2.2

ALC Apollo 43 www.smartcart.co.uk 0330 311 95 35 0330 311 95 35 www.smartcart.co.uk ALC Apollo 43